

Roll No

ME-6003 (CBGS)

B.E. VI Semester

Examination, May 2019

Choice Based Grading System (CBGS)

Heat and Mass Transfer

Time : Three Hours

Maximum Marks : 70

- Note:** i) Attempt any five questions out of eight.
 ii) All questions carry equal marks.
 iii) The standard HMT data book is permitted in exam.

- State Fourier's law of heat conduction. How this law is similar to ohm's law. Explain.
 - A plastic pipe ($K=0.5W/mk$) of ID 3cm and OD 4cm carries a fluid of average temperature $100^{\circ}C$ and $n=300 W/m^2k$ The rate of heat transfer per unit length is $500 W/m$. Find.
 - Outside surface temperature of pipe
 - The overall heat transfer coefficient based on out side area.
- A 3 cm diameter pipe at $100^{\circ}C$ is losing heat at the rate of $100 W$ per m length of pipe to the surrounding air at $20^{\circ}C$. This is to be reduced to a minimum value by providing insulation . The following insulation materials are available:
 Insulation A=Quantity= $3.15 \times 10^{-3} m^3$ per m length of pipe
 Thermal conductivity= $5W/m deg$.
 Insulation B Quantity= $4 \times 10^{-3} m^3$ per m length of pipe. Thermal conductivity= $1W/m deg$.
 Examine the position of better insulating layer relative to pipe. What percentage saving in heat dissipation results from the arrangement.
- Define fin effectiveness.

- The rate of heat transfer
 - Temperature at the fin tip
 - Heat transfer rate from the same fin geometry of the stainless steel fin is replaced by a fictitious fin with infinite thermal conductivity.
 - Rate of heat transfer from the wall area covered by the fin if the fin was not used.
- State Buckingham π theorem. What are it's merits?
 - Air at $20^{\circ}C$ and 1 atm flows over a flat plate at $40m/sec$. The plate is 80 cm long and is maintained at $60^{\circ}C$. Assume unit length in Z direction, calculate the heat transfer rate from the plate. Properties of air at $40^{\circ}C$ are $Pr = 0.7$, $k = 0.02723 W/mk$, $C_p = 1.007kJ/kg K$ and $\mu = 1.906 \times 10^{-5} kg/ms$.
- What is limitation of LMTD method. How ϵ -NTU method superior to it.
 - Explain Fick's law of diffusion. What is mass diffusivity
- A $4kg/sec$ of product stream from a distillation column is to be cooled by $3kg/sec$ water stream in a counterflow heat exchanger. The hot and cold stream inlet temperatures are $400K$ and $300K$ respectively and the area of heat exchanger is $30m^2$. If the overall heat transfer coefficient is estimated to be $820W/m^2K$. Determine the outlet temperature of both fluid if the specific heat is product stream is $2500J/kg k$.
- Define the following: http://www.rgpvonline.com
 - Emissivity of surface.
 - Black body.
 - Film wise condensation.
 - Planck's distribution law.
- Explain different regime of boiling.
 - The filament of a $75 W$ light bulb may be considered a black body radiating into black enclosure at $80^{\circ}C$. The filament dia is $0.10m$ and length is $60 mm$. Considering radiation only, determine filament temperature.